



ROUND HEADS FOR WOOD SCREWS

ASME B18.6.1

Nominal Size	A		H		J		T		M		G		N	Phillips Driver Size		
	Head Diameter		Height of Head		Width of Slot		Depth of Slot		Dimensions of Recess							
	Max	Min	Max	Min	Max	Min	Max	Min	Diameter		Depth				Width	
2	.162	.146	.069	.059	.031	.023	.048	.037	.114	.101	.064	.042	.018	1		
4	.211	.193	.086	.075	.039	.031	.058	.044	.130	.117	.083	.063	.019	1		
5	.236	.217	.095	.083	.043	.035	.063	.047	.154	.141	.074	.046	.027	2		
6	.260	.240	.103	.091	.048	.039	.068	.051	.162	.149	.084	.056	.027	2		
7	.285	.264	.111	.099	.048	.039	.072	.055	.170	.157	.092	.066	.028	2		
8	.309	.287	.120	.107	.054	.045	.077	.058	.178	.165	.101	.075	.030	2		
9	.334	.311	.128	.115	.054	.045	.082	.062	.186	.173	.110	.084	.030	2		
10	.359	.334	.137	.123	.060	.050	.087	.065	.195	.182	.119	.093	.031	2		
12	.408	.382	.153	.139	.067	.056	.096	.073	.249	.236	.125	.099	.032	3		
14	.457	.429	.170	.155	.075	.064	.106	.080	.265	.252	.142	.116	.034	3		



OVAL HEADS FOR WOOD SCREWS

ASME B18.6.1

Nominal Size	A		H	O		J		T		M		G		N	Phillips Driver Size		
	Head Diameter		Side Height	Height of Head		Width of Slot		Depth of Slot		Dimensions of Recess							
	Max	Min		Ref	Max	Min	Max	Min	Max	Min	Diameter		Depth			Width	
4	.225	.195	.067	.104	.084	.039	.031	.059	.049	.136	.123	.094	.077	.019	1		
5	.252	.220	.075	.116	.095	.043	.035	.067	.055	.158	.145	.085	.061	.028	2		
6	.279	.244	.083	.128	.105	.048	.039	.074	.060	.178	.165	.105	.080	.030	2		
8	.332	.292	.100	.152	.126	.054	.045	.088	.072	.205	.192	.131	.106	.033	2		
9	.358	.316	.108	.164	.137	.054	.045	.095	.078	.216	.203	.144	.119	.034	2		
10	.385	.340	.116	.176	.148	.060	.050	.103	.084	.261	.248	.142	.118	.037	3		
12	.438	.389	.132	.200	.169	.067	.056	.117	.096	.283	.270	.165	.140	.040	3		